

# Ultra Concentrated No-Rinse Speed Stripper

# **DESCRIPTION**

Bolt is an ultra concentrated formula that quickly penetrates and removes even extreme floor finish build-up. Excellent wetting and slow drying features save time and labor. Compared to leading floor strippers Bolt™ is 2 to 4 times more active. It contains no caustics, and does not require a neutralizing flood rinse.

# PRODUCT FEATURES / BENEFITS

- Ultra concentrated
- Lightning Fast Stripping Performance
- Superb wetting system, remains wet longer to eliminate rewetting which adds extra work.
- Requires no flood rinse or neutralization step / Saves time by eliminating neutralizing and rinsing
- Low odor formula for use in virtually any situation.
- Low foaming makes cleanup easy with automatic scrubbers and wet pick-up vacuums.

# DIRECTIONS FOR USE

For the rapid removal of all floor finishes and waxes from resilient flooring including: vinyl, vinyl asbestos, vinyl composition, asphalt, linoleum, and rubber tiles. Also ideal for finished non-resilient surfaces such as: terrazzo, marble, ceramic, quarry tile, concrete, and poured epoxy flooring. Although excellent for any type of equipment, greatest savings are realized when using automatic scrubbing equipment.

Follow dilution recommendations below. Dilute using cold water only.

Light/Normal Buildup: 4 oz per gallon of water (1:32) Heavy Buildup (Burnished): 16 oz per gallon of water (1:8)

### **Quart Dilutions:**

1 quart per 8 gallons of water (1:32) Light/Normal Buildup: Heavy Buildup (Burnished): 1 quart per 2 gallons of water (1:8) Allow to stand for 3 to 5 minutes, scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Remove solution and old liquified finish with a wet vacuum and allow floor to dry completely. If desired, a rinsing step can be added. Apply recommended NCL Floor Finish as per instructions.

Note: Asphalt tile, Linoleum, and other sensitive floor surfaces may be damaged by contact with stripping solution. We recommend that a spot test be conducted before general

# **SPECIFICATIONS**

Color	Clear	F
Odor	Sassafras	
pH	12.7 ± 0.3	
Upper Cloud Point	> 130°F	5
Lower Cloud Point	< 33°F	F
Viscosity (cps)	< 5	L
Water Solubility	Complete	S

Finish Removal		Excellent
Damage to Resilie	ent Tiles	Minimal
Density (lbs/gal) .		7.9 ± 0.1
Specific Gravity (	g/cc)	0.95 ± 0.01
Free Rinsing		Yes
Low Foaming		Yes
Shelf Life	1 year minimum in origi	nal unonened container

# SAFETY INFORMATION

**DANGER:** CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. HARMFUL IF SWALLOWED. IN CONTACT WITH SKIN OR IF INHALED. MAY CAUSE RESPIRATORY IRRITATION. KEEP OUT OF THE REACH OF **CHILDREN** 

## **Precautionary statement:**

#### Prevention:

Do not breathe mist or vapor. Use only in well-ventilated areas. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep out of reach of children

#### Response:

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/ doctor. Wash contaminated clothing before reuse.

Storage: Store locked up. Store in a well-ventilated place. Keep

Disposal: Dispose of contents/container in accordance with local/ regional/national/international regulations.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

For Commercial and Industrial Use Only



World Class Cleaning & Hygiene Solutions™

401 N. 10th Street • Philadelphia, PA 19123 1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517 www.nclonline.com • e-mail:info@nclonline.com

