



# IMPRESSIONS™

Brilliant Gloss / Ultra Wear Floor Finish

## DESCRIPTION

A proprietary blend of synergistic polymers provide uncompromised benefits of immediate wet look gloss and outstanding wearability. Sophisticated integrated components allow for rapid drying, enhanced leveling and superior repairability. This versatile product can be used in many varied environments and maintained with both high & low speed equipment.

## PRODUCT FEATURES / BENEFITS

- Very hard wear surface / Extremely scuff resistant
- Enhanced leveling; repairs easily / Usable by any personnel in many applications
- Super brilliant gloss / Maximizes appearance & user appeal
- Fast drying / Allows faster re-coating and less waiting
- Pure thermoplastic polymers / Very responsive to multi-speed polishing

## DIRECTIONS FOR USE

**Floor Preparation:** Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

**Application:** Using a clean mop or applicator apply thin uniform coats of IMPRESSIONS™ Brilliant Gloss / Ultra Wear Floor Finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

**High Speed Buffing and Burnishing:** IMPRESSIONS™ Brilliant Gloss / Ultra Wear Floor Finish is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an approved buffing pad. For spray buffing, mop-on or autoscrubber restoring use a preferred NCL gloss restorer.

**Routine Maintenance:** Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

## SPECIFICATIONS

|                             |                            |                                |   |
|-----------------------------|----------------------------|--------------------------------|---|
| Type .....                  | Pure acrylic polymers      | Multi-Speed Buffing .....      | Yes   |
| pH .....                    | 8.2 ± 0.3                  | Leveling .....                 | Excellent                                     |
| Drying Time (minutes) ..... | 20-30                      | Black Mark Resistant .....     | Superior                                      |
| Color .....                 | White, opaque liquid       | Scuff Resistance .....         | Superior                                      |
| Odor .....                  | Acrylic                    | Soil Resistance .....          | Superior                                      |
| Film Appearance .....       | Clear                      | Durability .....               | Excellent                                     |
| Powdering .....             | None                       | Recoatibility .....            | Excellent                                     |
| Flash Point .....           | None                       | Removability .....             | Excellent                                     |
| Freeze thaw stable .....    | Yes (3 Freeze Thaw Cycles) | Immediate Wet Look Gloss ..... | Outstanding                                   |
| Detergent Resistant .....   | Yes                        | Slip Resistant .....           | Yes   |
|                             |                            | Shelf Life .....               | 1 year minimum in original unopened container |

## SAFETY INFORMATION

**KEEP OUT OF THE REACH OF CHILDREN.**

### Precautionary statement

**Prevention:** Observe good industrial hygiene practices.

**Response:** Wash thoroughly after handling.

**Storage:** Store away from incompatible materials.

**Disposal:** Dispose of contents/container in accordance with local regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at [www.nclonline.com](http://www.nclonline.com)

KEEP FROM FREEZING

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing Material  
As to Slip Resistance Only  
18EL



401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
[www.nclonline.com](http://www.nclonline.com) • e-mail:[info@nclonline.com](mailto:info@nclonline.com)