



VIVID

Interactive Floor Finish Laminator & Maintainer

DESCRIPTION

An interactive blend of cleaners, penetrants, gloss enhancers and moisturizers that laminate the floor finish surface to provide maximum gloss, flexibility and durability. This versatile product can be used by mop-on restoration method, spray buffing or through an auto scrubber. Outstanding gloss and durability are the hallmark of this unique maintainer.

PRODUCT FEATURES / BENEFITS

- Contains proprietary gloss enhancers / Laminates floor finish surface & provides maximum gloss
- Contains moisturizers / Enhances floor finish flexibility & repairability
- Cleans, moisturizes & repairs in 1 step / Labor & material savings
- Multi-purpose formula / Use by mopping, spraying or with automatic scrubber
- Adds plasticizers to the floor finish / Restores elasticity and eliminates build-up associated with other restoration methods

DIRECTIONS FOR USE

This multipurpose formula can be used in many varied high gloss floor finish programs and environments. Applications include use as mop on restorer, spray buff or with auto-scrubber. Many methods can be combined for customized & peak floor care performance.

Maintenance: Remove surface dust and dirt daily by dust mopping. When scratches and scuffs become visible, apply maintainer solution diluted as above, allow to dry, and polish floors. For unusually stubborn black heel marks, use undiluted laminator as a spray buff and apply directly to those areas and burnished while still wet.

Preparation of Floors: The floor surface must contain a base wear coat of 4 to 6 coats of a proven compatible thermoplastic floor finish which has been allowed to cure for a minimum of 24 hours. Depending on soil conditions, the floor should be either dust mopped (if relatively clean) or damp mopped with a free rinsing neutral detergent and allowed to dry.

Application for Mop-On Restoration: Dilute one part maintainer with 4 parts of clean cool water into a clean wringer bucket.

Agitate the solution briefly to insure complete mixing. Apply restorer using a clean mop, wringing the mop only hard enough so that the solution is not dripping. Apply evenly to the floor, frequently going back to the bucket for refills, and allow to dry. As soon as the floor is visibly dry it may be burnished to a high gloss using the recommended high speed polishing pad and equipment.

Application for Spray Buffing: For use with all conventional polishers, high speed polishers and burnishing equipment. Place the product into a trigger sprayer or other suitable spraying device. Apply a very light mist to a small area directly in the path of the floor machine, and immediately buff to a high gloss. A heavier application of the product may be made directly on black heel marks or heavily worn areas.

Application for Auto-Scrubber Restoration: Dilute 8 oz. of maintainer with each gallon of clean cool water in an auto-scrubber equipped with recommended floor pads. Apply solution, single or double scrub, and pick up solution. As soon as floor is visibly dry, it may be burnished to a high gloss using the recommended high speed polishing pads and equipment.

SPECIFICATIONS

Type.....	Blended emulsifiers	Detergent Resistant	Yes
pH.....	9.5 ± 0.3	Lamination.....	Excellent
Drying Time (minutes)	10-20	Leveling	Excellent
Color.....	White, opaque liquid	Black Mark Resistant.....	Superior
Odor.....	Citrus	Scuff Resistance.....	Superior
Film Appearance	Clear	Soil Resistance.....	Superior
Powdering	None	Durability.....	Excellent
Flash Point.....	None	Recoatibility.....	Excellent
Slip Resistant	Yes	Removability.....	Excellent
Freeze thaw stable	Yes (3 Freeze Thaw Cycles)	Shelf Life.....	1 year minimum in original unopened container

SAFETY INFORMATION

KEEP OUT OF THE REACH OF CHILDREN.

Precautionary statement

Prevention: Observe good industrial hygiene practices.

Response: Wash thoroughly after handling.

Storage: Store away from incompatible materials.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as


defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at www.nclonline.com

KEEP FROM FREEZING.


For Commercial and Industrial Use Only



BUFFING COMPOUND



CLASSIFIED Floor Coating and Finishing Material As to Slip Resistance Only 18EL



401 N. 10th Street • Philadelphia, PA 19123
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517
www.nclonline.com • e-mail:info@nclonline.com